



DECLARATION
OF PERFORMANCE

**GYPROC
SOUNDBLOC MR
PLASTERBOARD**

<p>1 Unique identification code of the product-type:</p>	<p>Gyproc SoundBloc Moisture Resistant</p>
<p>2 Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4):</p>	<p>Gyproc SoundBloc Moisture Resistant: 12.5mm, 15mm EN 520 - DH1</p>
<p>3 Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:</p>	<p>Plasterboard lining in all reaction to fire requirements</p>
<p>4 Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):</p>	<p>Saint-Gobain Construction Products (IRL) Ltd. Registered in Ireland, Company No. 11815 Unit 4 Kilcarbery Business park, Nangor Road, Dublin 22; D22 R2Y7, Tel: +353 (0) 1 629 8400</p>
<p>5 Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):</p>	<p>N/A</p>
<p>6 System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V:</p>	<p>System 4</p>

7 In case of the declaration of performance concerning a construction product covered by a harmonised standard:	EN 520: 2004+A1: 2009
8 Notified Body/Bodies:	MPA Hannover (Materialprufanstalt Hannover Bauwesen und Produktionstechnik), Notified body No. 0764 issued reports relating to System 3 classification requirements for reaction to fire
9 In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued	N/A
10 Declared performance according to EN 520: 2004 + A1:2009:	The characteristics in the table below apply to all products mentioned in 2 above.

Essential Characteristics	Performance	Harmonised technical specification
Shear strength	NPD	EN 520: 2004 + A1:2009
Reaction to fire	A2-s1, d0	
Water vapour resistance factor	10	
Longitudinal flexural strength	≥ 550N (12.5mm)	
	≥ 650N (15mm)	
Transverse flexural strength	≥ 210N (12.5mm)	
	≥ 250N (15mm)	
Impact resistance	Performance declared is for the system of which the product is a part. Refer to Gyproc literature	
Direct airborne sound insulation		
Acoustic absorption		
Thermal resistance (as conductivity)		0.25 W/mk

11 Appropriate Technical Documentation and/or Specific Technical Documentation:	The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 10. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.
--	--

Signed for and on behalf of the manufacturer by:



Kieran Holohan
Managing Director

Saint-Gobain Construction Products (Irl) Limited
11/05/26

Freephone ROI: 1800 744480
Freephone NI: 0845 3990159
Email: tech.ie@saint-gobain.com
www.gyproc.ie

Gyproc, Gypframe and Glasroc are all registered trade names of Saint-Gobain Construction Products (Irl) Limited. Isover is a registered trade name of Saint-Gobain.

Saint-Gobain Construction Products (Irl) Limited reserves the right to revise product specifications without notice. The information in this document was correct to the best of our knowledge at the time of publication. It is the user's responsibility to ensure that it remains current prior to use. The information in this document is for guidance only and should not be read in isolation. Users should read and familiarise themselves with all the information contained in this document and ensure that they are fully conversant with the products and systems being used, before subsequent specification or installation. For a comprehensive and up-to-date library of information visit the Gyproc website at: www.gyproc.ie



DOP number attributed by manufacturer:
DOP_PB_SOUNDBLOC_MR

