



PRODUCT DATA SHEET

GYPROC DRYWALL PRIMER

Overview

Gyproc Drywall Primer is a primer for new plasterboard surfaces to prepare them for painting.

Where To Use

Use it after joint treatment is complete to protect plasterboard surfaces from UV degradation and to equalise suction and texture for painting.

Standards

Gyproc Drywall Primer are manufactured under a quality system independently audited and certified as conforming with ISO 9001.

Product Information

Composition

This product is made up of a polymer dispersion based primer.

Colour

Magnolia.

Nominal volume (litres)

10L

Minimum temperature

Ambient and background temperature must be maintained above 5°C until fully dry.

Performance

Here we only provide performance information related to the product. Please see the White Book online for system-dependent performance.

Maximum VOC content (g/l)	<10
----------------------------------	-----

Limitation of use

Gyproc Drywall Primer may be used as a base for most wallcoverings, but solvent-based wall covering adhesives should not be used.

Effect of temperature

Ambient and background temperature must be maintained above 5°C until fully dry. The product should be stored between 5°C and 30°C.

Application

Background preparations: plasterboard

Board and joint treatment surfaces should be dry, clean and dust-free before application.

Can be applied by brush or medium-pile roller.

Mixing up

Stir before use, do not dilute.

Coverage per litre (m²)	15 (one coat)
---	---------------

Painting and wallpapering

Painting

Allow the primer to fully dry before painting.

Sitework

Storage

Store and use in temperature range of 5-30°C. Avoid stacking more than four tubs high to prevent damage to the packaging.

Handling

Gyproc fully accepts its responsibilities as a supplier of building materials and systems in accordance with the Safety, Health and Welfare at Work Act 2005.

To reduce the risk associated with manual handling, employers and workers should comply with the Manual Handling of Loads Regulations 2007 (S.I. No. 299/2007) and consult the Health and Safety Authority's (HSA) guidance on safe manual handling practices.

Employers are required to carry out suitable and sufficient risk assessments and to implement control measures to eliminate or reduce the need for manual handling wherever reasonably practicable.

Workers should use safe lifting and movement techniques as trained, remain alert to manual handling hazards, and report any issues promptly in accordance with their employer's safety procedures.

Safety Data Sheet

Safety Data Sheet (SDS) available [Click here](#).

Shelf life

This product has a shelf life of 12 months and is marked with a use-by-date.

Packaging overview

10 litre plastic tub, supplied palletised.

Quantity per pallet	48 tubs
----------------------------	---------

Environmental

Recyclability

This product cannot be recycled.

Disposal

Waste should be disposed of in accordance with local authority requirements. Do not empty into drains or watercourses.

Freephone ROI: 1800 744480

Freephone NI: 0845 3990159

Email: tech.ie@saint-gobain.com

www.gyproc.ie

Gyproc, Gypframe and Glasroc are all registered trade names of Saint-Gobain Construction Products (Irl) Limited. Isover is a registered trade name of Saint-Gobain.

Saint-Gobain Construction Products (Irl) Limited reserves the right to revise product specifications without notice. The information in this document was correct to the best of our knowledge at the time of publication. It is the user's responsibility to ensure that it remains current prior to use. The information in this document is for guidance only and should not be read in isolation. Users should read and familiarise themselves with all the information contained in this document and ensure that they are fully conversant with the products and systems being used, before subsequent specification or installation. For a comprehensive and up-to-date library of information visit the Gyproc website at: www.gyproc.ie



© Saint-Gobain Construction Products (Irl) Limited
September 2025 | PDS_DSA_DRYWALL_PRIMER

