

## PRODUCT DATA SHEET

# RIGITONE® EDGE 12/25Q

### Introduction

Rigitone 12/25Q is a perforated gypsum acoustic board used in conjunction with **CasoLine MF**, **CasoLine CURVE** or **GypLyner** systems. It creates a totally monolithic surface in acoustic ceilings, islands or vertical wall absorbers where aesthetic design and reverberation control are desired.

## Product Description

Rigitone 12/25Q comprises a 12.5mm gypsum core, with a regular geometric pattern of 12mm square perforations at 25mm centres. The reverse of the board incorporates an acoustic fleece which provides sound absorption performance.

## Board Performance

Rigitone boards provide sound absorption when used in conjunction with an air space behind the ceiling or wall. Tests have been carried out to *BS EN 20354: 1993* and *ISO 354: 1985* with a 200mm plenum depth.

The single figure rating practical sound absorption coefficients  $\alpha_w$ , and sound absorption classes, are calculated in accordance with *BS EN ISO 11654: 1997*. The Noise Reduction Coefficient (NRC) is calculated in accordance with *ASTM C423-90a: 1992*.


Rigitone boards can be used in conjunction with the **CasoLine curve** system to form a curved finish with a minimum radius of 5000mm.

## PHYSICAL PROPERTIES

<b>Board size</b>	2000x1200mm
<b>Board thickness</b>	12.5mm
<b>Perforation size</b>	12mm squares
<b>Perforation spacing</b>	25mm centres
<b>Perforated area</b>	23%
<b>Edge type</b>	Chamfered (sanded and primed)
<b>Acoustic class</b>	Class A
<b><math>\alpha_w</math> (up to)</b>	0.90
<b>Reaction to fire</b>	A2-s1,d0
<b>Weight (approx)</b>	9.5 kg/m <sup>2</sup>
<b>Moisture resistance</b>	up to 70% RH
<b>Tissue colour</b>	Black (White tissue available on request)

## Board Performance continued

RIGITONE EDGE 12/25Q		PRACTICAL ABSORPTION COEFFICIENT $\alpha_p$						$\alpha_w$	CLASS
PLENUM MM	INSULATION MM	125	250	500	1000	2000	4000		
200		0.40	0.80	0.90	0.65	0.60	0.60	0.65	C
200	60	0.60	0.90	0.95	0.95	0.80	0.75	0.85	B
200	140	0.85	0.90	0.90	0.90	0.85	0.75	0.90	A



Class A acoustic class achieved with a plenum depth of 200mm and 140mm Isover Comfort 35 Insulation.

## Application and installation

### Handling and storage

Rigitone boards should be stored flat on a level surface and protected from dampness. To avoid damage to the special acoustic tissue bonded to the back face, Rigitone boards should not be pulled over the edges of the stack of boards below.

### Installation

Rigitone boards are installed in the **CasoLine MF** grid system. Where plenum depths are restricted, use the **GypLyner** system. For full details of installation, refer to the **Gyproc White Book**.

Installation of Rigitone requires a range of accessories and tools. It is important to ensure these are requested at time of order to allow trouble-free installation.

### Jointing and finishing

Rigitone acoustic ceiling boards have a pre-sanded and pre-primed edge and do not require any pre-treatment to the board edges prior to installation. The boards have a chamfered edge to all four sides, simplifying the jointing process, without the need of specialist spacing tools.

Matt emulsion paint should be applied with a paint roller. Do not use a spray system as this will affect the acoustic properties of the board.

### Fixing

Fixings to the system should always be made into the metal grid or to supplementary framing. Adjustment of the primary grid may be required to support particularly heavy loads. Refer to the **Gyproc White Book** for full design information regarding the relevant system.

### Environment

Rigitone boards are unsuitable for use in areas subject to continuously damp or humid conditions above 70% RH, or in elevated temperatures consistently above 49°C. They can be exposed to freezing temperatures without risk of damage.

### Recyclability

The gypsum core of Rigitone boards is 100% recyclable. **CasoLine MF**, **CasoLine curve** and **GypLyner** are also 100% recyclable.

## Product standards

All Rigitone Edge boards are manufactured under management systems which have been independently audited and certified as conforming with *ISO 14001: 2015* and *ISO 50001: 2018*. All Rigitone products conform to *EN 14190: 2005* Gypsum plasterboard from reprocessing – definitions, requirements and test methods.

## Maintenance

Rigitone boards can be redecorated using a roller and suitable matt emulsion paint. The paint should not be applied with a spray diffuser as this will impair the acoustic performance.

Freephone ROI: 1800 744480

Freephone NI: 0845 3990159

Email: tech.ie@saint-gobain.com

[www.gyproc.ie](http://www.gyproc.ie)

Gyproc, Gyproframe and Glasroc are all registered trade names of Saint-Gobain Construction Products (Irl) Limited. Isover is a registered trade name of Saint-Gobain.

Saint-Gobain Construction Products (Irl) Limited reserves the right to revise product specifications without notice. The information in this document was correct to the best of our knowledge at the time of publication. It is the user's responsibility to ensure that it remains current prior to use. The information in this document is for guidance only and should not be read in isolation. Users should read and familiarise themselves with all the information contained in this document and ensure that they are fully conversant with the products and systems being used, before subsequent specification or installation. For a comprehensive and up-to-date library of information visit the Gyproc website at: [www.gyproc.ie](http://www.gyproc.ie)



© Saint-Gobain Construction Products (Irl) Limited  
March 2024 | PDS\_CTB\_EDGE\_12-25Q

