


# Product Data Sheet

## Gyprex Bio 600mm

Gyprex Bio is a vinyl-faced gypsum tile that's smooth and wipeable. It contains a biocide to slow fungi and bacteria growth.

### Where to use

Use it with the GypCeiling Grid to form a demountable suspended ceiling. Gyprex Bio is ideal for commercial ceiling installations that demand the highest levels of hygiene.



## Product information

### Composition

Gypsum core with biocide and a vinyl face covering.

### Face colour

White.

### Where to buy

[Click here.](#)

## DIMENSIONS AND WEIGHTS

Lengths available (mm)	594
Width (mm)	594
Nominal thickness (mm)	8
Length: maximum tolerance (mm)	+2
Length: minimum tolerance (mm)	-1
Width: maximum tolerance (mm)	+2
Width: minimum tolerance (mm)	-1
Perforated area (%)	0
Edge type availability	A
Weight (kg/m <sup>2</sup> )	6.2

# Product Data Sheet

## Gyprex Bio 600mm

### Performance

Here we only provide performance information related to the product. Please see the White Book online for system-dependent performance.

### Standards

EN 14190:2014.

Declarations of Performance (DoP) available [Click here](#).

Reaction to fire	B-s1, d0
Specialist performance	Integral Biocide which limits the growth of fungi and bacteria including MRSA, E. coli O157 and Salmonella.
Moisture resistance (maximum % RH)	90
Water vapour resistivity (MNs/g)	45
Loading capability (kg/tile)	3
Light reflectance (%)	88
Maximum continuous temperature (°C)	49

### Limitations of use

Gyprex ceiling tiles have been tested in accordance with BS 8290: Part 2, and are suitable for high humidity conditions; 90% RH at 25°C.

The tiles are not suitable for use above 90% RH, or in temperatures consistently above 49°C. They can be exposed to freezing temperatures without a risk of damage.

### Fixtures

Don't use Gyprex products to support fixtures without using a pattress. Hang lights and similar fixtures separately from wires or fix to structural soffit.

### Installation guidance

Please see our White Book online for more information about installing and handling British Gypsum systems.

### Painting

The tile's vinyl surface is not suitable for painting.

# Product Data Sheet

## Gyprex Bio 600mm

### Sitework

#### Storage

Gyprex products should be stored flat on a level surface and protected from dampness.

#### Safety Data Sheet

Safety Data Sheet (SDS) available. [Click here.](#)

#### Packaging overview

Tiles per pallet	100
Coverage per pallet (m <sup>2</sup> )	36
Weight per pallet (tonnes)	0.3

### Environmental

#### Recyclability

The gypsum core of Gyprex tiles is 100% recyclable.

#### Disposal

British Gypsum operates a Plasterboard Recycling Service; please call 0800 6335040 for further information. Alternatively, segregate the product from non-gypsum waste for recycling where possible, and dispose of it according to local authority requirements.



"Gyproc", "Thistle", "ThistlePro", "Gypframe" and "Glasroc" are all registered trademarks of Saint-Gobain Construction Products UK Limited. "Isover" is a registered trademark of Saint-Gobain Isover (French legal entity) and "Okarno" is a registered trademark of Okarno Limited.

Saint-Gobain Construction Products UK Limited is a limited company registered in England under company number 734396, having its registered office at Saint-Gobain House, East Leake, Loughborough, Leicestershire, LE12 6JU, UK. Saint-Gobain Construction Products UK Limited trades as British Gypsum for part of its business activities.

British Gypsum reserves the right to revise product specification without notice. The information herein should not be read in isolation as it is meant only as guidance for the user, who should always ensure that they are fully conversant with the products and systems being used and their subsequent installation prior to the commencement of work. For a comprehensive and up-to-date library of information visit the British Gypsum website at: [british-gypsum.com](http://british-gypsum.com). For information about products supplied by Artex Limited or Saint-Gobain Isover please see their respective websites.

"British Gypsum" is a registered trademark of Saint-Gobain Construction Products UK Limited.