

GYPROC GLASROC X SEALANT

Declaration of Performance

SEAL101

1 Unique identification code of the product-type:

Glasroc X Sealant

2 Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

Glasroc X Sealant, EN 15651-1: 2012

3 Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

Sealant for non-structural use in joints in buildings

4 Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

Saint-Gobain Construction Products (Ir) Limited
Registered in Ireland, Company No. 11815
Unit 4 Kilcarbery Business Park, Nangor Road,
Dublin 22, D22 R2Y7

Tel: +353 (0) 1 6298400

5 Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

N/A

6 System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 3

7 In case of the declaration of performance concerning a construction product covered by a harmonised standard:

EN 15651-1: 2012

GINGER CEBTP, Notified Body No. 0074

8 In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

N/A

9 Declared performance/s:

The characteristics in the table below apply to all products mentioned in 2 above.

Substrate: Anodised Aluminium **Tested Class:** 25 LM CC **Scope:** Facade EXT/INT

Essential Characteristics	Test standards	Performance	Harmonised technical specification
Reaction to Fire	EN 13501-1: 2007 + A1: 2009	Class E	EN 15651-1: 2012
Release of dangerous substances	-	None	EN 15651-1: 2012

Water tightness and air-tightness determined by:


Resistance to flow	EN ISO 7390	≤3mm	EN 15651-1: 2012
Loss of volume	EN ISO 10563	≤10%	EN 15651-1: 2012
Adhesion / cohesion properties at maintained extension after water immersion (23°C)	EN ISO 10590	NF	EN 15651-1: 2012
Adhesion / cohesion properties (-30°C)	EN ISO 8339 modified	≤0.9MPa	EN 15651-1: 2012
Adhesion / cohesion properties at maintained extension (-30°C)	EN ISO 8340 modified	NF*	EN 15651-1: 2012
Durability	EN ISO 8340 EN ISO 9047 EN ISO 10590	Pass	EN 15651-1: 2012

* NF - No failure according to EN ISO 11600

10 The performance of the products identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:



Pádraig Barry
Managing Director

Saint-Gobain Construction Products (Irl) Limited
Kilcarbery Office
16/06/2021

Freephone ROI: 1800 744480
Freephone NI: 0845 3990159
Email: tech.ie@saint-gobain.com
www.gyproc.ie

Gyproc, Gyproframe and Glasroc are all registered trade names of Saint-Gobain Construction Products (Irl) Limited. Isover is a registered trade name of Saint-Gobain.

Saint-Gobain Construction Products (Irl) Limited reserves the right to revise product specifications without notice. The information in this document was correct to the best of our knowledge at the time of publication. It is the user's responsibility to ensure that it remains current prior to use. The information in this document is for guidance only and should not be read in isolation. Users should read and familiarise themselves with all the information contained in this document and ensure that they are fully conversant with the products and systems being used, before subsequent specification or installation. For a comprehensive and up-to-date library of information visit the Gyproc website at: www.gyproc.ie