

# GYPROC

# RIGITONE 8-15-20 SUPER

Product Data Sheet



## Product Description

Rigitone 8-15-20 SUPER comprises a 12.5mm gypsum core, with an irregular array of 8mm, 15mm and 20mm circular perforations. The reverse of the board incorporates an acoustic fleece which provides sound absorption performance.

## Board Performance

Rigitone boards provide sound absorption when used in conjunction with an air space behind the ceiling or wall. Tests have been carried out to *BS EN 20354: 1993* and *ISO 354: 1985* with either a 50mm or 200mm plenum depth.

The single figure rating practical sound absorption coefficients  $\alpha_w$ , and sound absorption classes, are calculated in accordance with *BS EN ISO 11654: 1997*. The Noise Reduction Coefficient (NRC) is calculated in accordance with *ASTM C423-90a: 1992*.


Rigitone boards can be used in conjunction with the **CasoLine curve** system to form a curved finish with a minimum radius of 5000mm.

## Physical properties

<b>Board size</b>	1960mm x 1200mm
<b>Board thickness</b>	12.5mm
<b>Perforation size</b>	8mm, 15mm and 20mm circles
<b>Perforation spacing</b>	Random/irregular
<b>Perforated area</b>	10%
<b>Edge type</b>	Square edge
<b>Acoustic class</b>	Class D
<b><math>\alpha_w</math> (up to)</b>	0.45
<b>NRC (up to)</b>	0.70
<b>Reaction to fire</b>	A2-s1,d0
<b>Weight (approx)</b>	10 kg/m <sup>2</sup>
<b>Moisture resistance</b>	up to 70% RH
<b>Tissue colour</b>	Black (White tissue available on request)

## Introduction

Rigitone 8-15-20 SUPER is a perforated gypsum acoustic board used in conjunction with **CasoLine MF**, **CasoLine curve** or **GypLyner** systems. It creates a totally monolithic surface in acoustic ceilings, islands or vertical wall absorbers where aesthetic design and reverberation control are desired.



Class D acoustic class achieved with a plenum depth of 200mm and 50mm Isover Acoustic Insulation laid over the back of the ceiling.

Rigitone 8-15-20 SUPER		Practical absorption coefficient $\alpha_p$						$\alpha_w$	Class	NRC
Plenum (mm)	Insulation (mm)	125	250	500	1000	2000	4000			
50		0.15	0.40	0.70	0.75	0.45	0.40	0.50	D	0.60
200		0.35	0.75	0.75	0.55	0.40	0.30	0.45	D	0.60
200	50	0.60	0.85	0.80	0.65	0.45	0.30	0.45	D	0.70

## Application and installation

### Handling and storage

Rigitone boards should be stored flat on a level surface and protected from dampness. To avoid damage to the special acoustic tissue bonded to the back face, Rigitone boards should not be pulled over the edges of the stack of boards below.

### Installation

Rigitone boards are installed in the **CasoLine MF** grid system. Where plenum depths are restricted, use the **GypLyner** system. For full details of installation, refer to the **Gyproc White Book**.

Installation of Rigitone requires a range of accessories and tools. It is important to ensure these are requested at time of order to allow trouble-free installation.

### Jointing and finishing

Rigitone acoustic ceiling boards have a pre-sanded and pre-primed edge and do not require any pre-treatment to the board edges prior to installation.

Matt emulsion paint should be applied with a paint roller. Do not use a spray system as this will affect the acoustic properties of the board.

### Fixtures

Fixings to the system should always be made into the metal grid or to supplementary framing. Adjustment of the primary grid may be required to support particularly heavy loads. Refer to the **Gyproc White Book** for full design information regarding the relevant system.

### Environment

Rigitone boards are unsuitable for use in areas subject to continuously damp or humid conditions above 70% RH, or in elevated temperatures consistently above 49°C. They can be exposed to freezing temperatures without risk of damage.

### Recyclability

The gypsum core of Rigitone boards is 100% recyclable. **CasoLine MF**, **CasoLine CURVE** and **GypLyner** are also 100% recyclable.

## Product standards

All Gyproc ceiling products are manufactured under management systems which have been independently audited and certified as conforming with *ISO 9001: 2001*. All Rigitone products conform to *EN 14190: 2005* Gypsum plasterboard from reprocessing – requirements and test methods.

## Maintenance

Rigitone boards can be redecorated using a roller and suitable matt emulsion paint. The paint should not be applied with a spray diffuser as this will impair the acoustic performance.

Freephone ROI: 1800 744480

Freephone NI: 0845 3990159

Email: tech.ie@saint-gobain.com

[www.gyproc.ie](http://www.gyproc.ie)

Gyproc, Gyproframe and Glasroc are all registered trade names of Saint-Gobain Construction Products (Irl) Limited. Isover is a registered trade name of Saint-Gobain.

Saint-Gobain Construction Products (Irl) Limited reserves the right to revise product specifications without notice. The information in this document was correct to the best of our knowledge at the time of publication. It is the user's responsibility to ensure that it remains current prior to use. The information in this document is for guidance only and should not be read in isolation. Users should read and familiarise themselves with all the information contained in this document and ensure that they are fully conversant with the products and systems being used, before subsequent specification or installation. For a comprehensive and up-to-date library of information visit the Gyproc website at: [www.gyproc.ie](http://www.gyproc.ie)