

DRILYNER WITH GYPROC HABITO



FIXING STRENGTH



SOUND PROOFING



DURABILITY



DriLyner is a wall lining system that provides a simple and effective solution to fix Gyproc Habito plasterboard directly to a block background using Gyproc Plasterboard Compound.

The key benefits to using this are minimal loss in your room space and allows minor surface irregularities to be taken out while services can be incorporated with a reduced level of chasing. Gyproc Plasterboard Compound is used as the adhesive dabs onto the block.

Installation

The board edge positions are marked on the wall, and Gyproc Plasterboard Compound is applied to the wall in dabs to support the boards. A continuous fillet / ribbon of Gyproc Plasterboard Compound is applied to the wall perimeter and around all services and openings. The plasterboards are then 'tapped' into position, lifted tight to the ceiling using a foot lifter and supported until the adhesive sets. Further boards are installed, lightly butted together, to complete the lining. The board can then be finished with a 2mm final coat of Gyproc Finish Plaster such as Gyproc Skimcoat or Gyproc Carlite Finish.

EXTERNAL WALLS

Components needed



Gyproc Plasterboard Compound

Gyproc Plasterboard Compound is for use in Gyproc DriLyner Systems for attaching plasterboards to masonry walls.



Gyproc Habito

A revolutionary new plasterboard that provides enhanced acoustic performance, impact resistance and direct fixing capabilities, allowing you to hang 15kg from one 5mm woodscrew.



Gyproc High Performance Drywall Screws

Designed for fixing Gyproc Habito plasterboard to metal and timber framing sections.



Gyproc Finish Plaster

Gyproc Skimcoat or Gyproc Carlite Finish are finishing plasters that provide the highest quality aesthetic finish.